

Display from CAplus

L# ANSWER 2 OF 4 CAPLUS COPYRIGHT 2003 ACS on STN

AN 1997:317775 CAPLUS

DN 126:295282

TI Fire-fighting aqueous emulsions consisting of water-insoluble fluorinated copolymers, ***surfactants***, fluorinated ***surfactants***, and water-miscible solvents

IN Garcia, Gilbert; Collette, Christian; Morillon, Elisabeth

PA Elf Atochem S.A., Fr.

SO Eur. Pat. Appl., 26 pp.

CODEN: EPXXDW

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
------------	------	------	-----------------	------

PI EP 765676	A1	19970402	EP 1996-401822	19960826
R: BE, CH, DE, DK, ES, FR, GB, IT, LI, NL, SE				
FR 2739295	A1	19970404	FR 1995-11385	19950928
JP 09124884	A2	19970513	JP 1996-244969	19960917
AU 9665863	A1	19970410	AU 1996-65863	19960926
CA 2186773	AA	19970329	CA 1996-2186773	19960927

PRAI FR 1995-11385 A 19950928

AB Fire-fighting emulsions consist of aq. dispersions contg.: (1) 0.5-10 wt.% of a water-insol. fluorinated copolymer prepd. from a monomer contg. a perfluorinated chain, a monomer contg. an ionic or ionizable chain, and/or a monomer contg. a nonionic chain, (2) 1-20 wt.% of a C5-18-branched or linear alkane ***surfactant***, (3) 0.5-10 wt.% of a fluorinated ***surfactant*** which, when present in aq. soln. at 1 g/L concn., gives rise to a surface tension at 20.degree. of 25 mN/m, and (4) 5-50 wt.% of a water-miscible solvent. The fluorinated copolymer is of general formula $-[M1]_x[M2]_y[M3]_z$, in which M1 is a C5-20- ***perfluoroalkyl*** acrylate or methacrylate; M2 is an acrylic, methacrylic, or vinylic monomer with an ionizable or hydrophilic group; M3 is an acrylic, methacrylic, or vinylic monomer with a nonionic (esp. hydrophobic) group; and $x = 50-95$, $y = 1-25$, and $z = 0-10$ (with an M1-M2 molar ratio of 1-10:1). A no. of ***surfactants*** are possible for the formulation, including ***betaines***, N,N-bis(2-carboxyethyl)amines, 2-alkyl(1-hydroxyethyl)imidazolines, quaternary ammonium chlorides, polyoxyalkylene monoethers, trialkylamine oxides, alkylbenzenesulfonic acids, etc.

IC ICM A62D001-00

DT Patent

LA French

EV979440227

L# ANSWER 101 OF 104 CAPLUS COPYRIGHT 2003 ACS on STN
AN 1972:33810 CAPLUS
DN 76:33810
TI

.beta.-[2-[2-(***Perfluoroalkyl***
)ethylsulfonylamino]ethyl]dimethylammonio
propionates

IN Bertocchio, Rene; Foulletier, Louis

PA Uguine Kuhlmann

SO Ger. Offen., 7 pp.

CODEN: GWXXBX

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI DE 2120868	A	19711118	DE 1971-2120868	19710428
DE 2120868	C2	19840517		
FR 2088941	A5	19720107	FR 1970-15836	19700430
FR 2128028	A6	19721020	FR 1971-6914	19710301
FR 2128028	B2	19730511		
PRAI FR 1970-15836		19700430		
FR 1971-6914		19710301		

AB The title compds., $\text{CF}_3(\text{CF}_2)_n\text{CH}_2\text{CH}_2\text{SO}_2\text{NHCH}_2\text{CH}_2\text{N}^+\text{Me}_2\text{-CH}_2\text{CH}_2\text{CO}_2^-$ (I, $n=5, 7$

or 9), useful as surfactants in e.g. textile industry, were prepd. by reaction of $\text{CF}_3(\text{CF}_2)_n\text{CH}_2\text{CH}_2\text{SO}_2\text{NHCH}_2\text{CH}_2\text{NMe}_2$ (II) with .beta.-propiolactone (III). Thus, reaction of 50 g II ($n=7$) with 6 g III in Me_2CO for 1 hr gave 49.1 g I ($n=7$).

IC C07C; C11D

DT ***Patent***

LA German

EV979440227

L8 ANSWER 7 OF 11 CAPLUS COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 1973:420652 CAPLUS

DOCUMENT NUMBER: 79:20652

TITLE: ***Surface*** - ***active*** fluorinated alkyl
sulfides

INVENTOR(S): Toukan, Sameeh Said; Hauptschein, Murray

PATENT ASSIGNEE(S): Pennwalt Corp.

SOURCE: Ger. Offen., 26 pp.

CODEN: GWXXBX

DOCUMENT TYPE: Patent

LANGUAGE: German

FAMILY ACC. NUM. COUNT: 3

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
DE 2239709	A1	19730222	DE 1972-2239709	19720811
CA 962281	A1	19750204	CA 1972-145564	19720623
GB 1395955	A	19750529	GB 1972-35227	19720727
NL 7210982	A	19730214	NL 1972-10982	19720811
FR 2150116	A5	19730330	FR 1972-29239	19720811
JP 48026714	A2	19730409	JP 1972-80040	19720811
JP 57047187	B4	19821007		

PRIORITY APPLN. INFO.: US 1971-171325 19710812

AB Eleven title compds., i.e. bis[2-[7-(trifluoromethyl)perfluorooctyl]ethylthiomethyl]methanol (I) [***40099-98-7***] and (F₃C)₂CF(CF₂)_nCH₂CH₂SX [II; n = 4 or 6; X = CH₂CH(OH)CH₂OH, CH₂CH₂CO₂H, CH₂CH₂NMe₂, CH₂CH₂NH₂,

4-pyridyl, 2-benzimidazolyl, 2-pyridimetyl, o-carboxyphenyl, or 3,5-dichloro-2-pyridyl] and their derivs., e.g. carbamates or chloroacetates, were prepd. without olefin formation in 33-100% yield by reaction of (F₃C)₂CF(CF₂)_nCH₂CH₂I (III) with (HSCH₂)₂CHOH (IV) and HSR, resp., in the presence of NaOH in a polar solvent, e.g. EtOH. I and II were partly used as ***surface*** - ***active*** agents and useful as insecticides. Thus, IV was added to NaOH-EtOH, the mixt. heated 5-10 min at .sim.50.deg., added to III (n = 6) in EtOH, and the mixt. refluxed 1 hr to give 81% I.

EV979440227

L9 ANSWER 20 OF 29 CAPLUS COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 1974:522705 CAPLUS

DOCUMENT NUMBER: 81:122705

TITLE: Oil- and water-repelling substance

INVENTOR(S): Kirimoto, Kazusuke; Hayashi, Takao

PATENT ASSIGNEE(S): Asahi Glass Co., Ltd.

SOURCE: Ger. Offen., 24 pp.

CODEN: GWXXBX

DOCUMENT TYPE: Patent

LANGUAGE: German

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
------------	------	------	-----------------	------

DE 2247111	A1	19740418	DE 1972-2247111	19720926
------------	----	----------	-----------------	----------

DE 2247111	B2	19760102		
------------	----	----------	--	--

PRIORITY APPLN. INFO.: DE 1972-2247111 19720926

AB Agents that imparted good oil- and water-resistance to cotton, polyester, and wool textiles with retention of the textile softness were copolymers (9 used) contg. 1.5-35% haloalkyl vinyl ether and .geq.25% fluoroalkyl (meth) ***acrylate***. Thus, cotton fabric treated with 75:20:50 copolymer of CH₂:CHCO₂(CH₂)₃CnF_{2n+1} (I, n = 7,9,11, and 13 in a 4:3:2:1 ratio), vinyl chloride (II) [75-01-4], and 2-chloroethyl vinyl ether [110-75-8] exhibited similar oil, water, and soil-resistance but higher softness values and better hand than cotton fabric treated with a 75:25 I-II copolymer.

EV979440227

L9 ANSWER 19 OF 29 CAPLUS COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER: 1974:522709 CAPLUS

DOCUMENT NUMBER: 81:122709

TITLE: Oil- and water-repellant material

INVENTOR(S): Kirimoto, Kazusuke; Hayashi, Takao; Kojima, Hiroaki

PATENT ASSIGNEE(S): Asahi Glass Co., Ltd.

SOURCE: Ger. Offen., 33 pp.

CODEN: GWXXBX

DOCUMENT TYPE: Patent

LANGUAGE: German

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
------------	------	------	-----------------	------

DE 2247182	A1	19740425	DE 1972-2247182	19720926
------------	----	----------	-----------------	----------

DE 2247182	B2	19750807		
------------	----	----------	--	--

DE 2247182	C3	19760311		
------------	----	----------	--	--

PRIORITY APPLN. INFO.: DE 1972-2247182 19720926

AB The addn. of polymers prepd. from C1-18 alkyl acrylates or methacrylates and methylolacrylamide or methylolmethacrylamide to fluoroalkyl

acrylate polymer oil-and waterproofing agents reduced the finishing costs while providing good oil and water repellency without any adverse effect on hand. Thus, a polymer prepd. from 73%

CH₂:CHCO₂CHCH₂(CF)_nCF₃ (a 4:3:2:1 mixt. of monomers with n = 4,6,8, and 10), 25% vinyl chloride, and 2% diacetoneacrylamide was mixed with an equal amt. of a 95:5 butyl ***acrylate*** -N-methylolacrylamide polymer [27157-48-8] and mixed with water to form an ***emulsion*** contg. 1% polymer. A 35:65 cotton-polyester fabric was padded with the

emulsion to provide wet add-on 80% and dried 3 min at 100.deg. and 4 min at 150.deg.. The finished fabric had a soft hand as well as good oil and water repellency.

EV979440227